

**NASA
Technical
Paper
3444**

1994

**Proof Test of the Computer
Program BUCKY for
Plasticity Problems**

James P. Smith
*Lyndon B. Johnson Space Center
Houston, Texas*



National Aeronautics and
Space Administration
Office of Management
Scientific and Technical
Information Program

(NASA-TP-3444) PROOF TEST OF THE
COMPUTER PROGRAM BUCKY FOR
PLASTICITY PROBLEMS (NASA) 10 p

N94-22960

Unclass

H1/39 0203384

1N-39
203384
P- 10

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000

**NASA
Technical
Paper
3444**

January 1994

**Proof Test of the Computer
Program BUCKY for
Plasticity Problems**

James P. Smith



Abstract

A theoretical equation describing the elastic-plastic deformation of a cantilever beam subject to a constant pressure is developed. The theoretical result is compared numerically to the computer program BUCKY for the case of an elastic-perfectly plastic specimen. It is shown that the theoretical and numerical results compare favorably in the plastic range. Comparisons are made to another research code to further validate the BUCKY results. This paper serves as a quality test for the computer program BUCKY developed at NASA Johnson Space Center.

Introduction

The ability to predict a structure's response to loading is a necessity in the field of structural analysis. Too often, a structure quickly becomes too complicated to analyze by hand calculations. In addition, when advanced topics such as material nonlinearity are introduced, the analysis becomes virtually impossible to perform by hand. In such cases, computer models must be developed to estimate the response of the structure.

Plastic analysis of structures has been incorporated into several finite element packages. However, nearly all current finite element programs are based on the h -version of the finite element method; only a few research codes based on the p -version of the finite element method are known to exist. The computer program BUCKY is a multi-element p -version finite element program that has the ability to perform elastic-plastic studies of structures.

The assumptions used in the development of BUCKY are few; the structure in question must be a two-dimensional plate structure in a state of plane stress. In addition, the material properties must be such that the plate is isotropic in nature and has work-hardening abilities. Proportional loading and no unloading are further assumptions of the computer method.

Using the tangent stiffness method, the p -version of the finite element is ideally suited for problems of plasticity. It will be shown that the cantilever beam example is effectively described with only two finite elements.

Problem Statement

We wish to find the exact theoretical deflection for a fixed cantilever beam of length L and thickness h subject to a uniform statically applied load q_0 over the beam span, as shown in Figure 1. As the beam is loaded, the extreme fibers ($z = \pm h/2$) experience higher stresses than the rest of the beam. Thus, these areas will yield before the remainder of the beam. The beam is assumed to have elastic-perfectly plastic material behavior, as shown in Figure 2.

With increasing load q_0 , the beam yields further until eventually the collapse load is reached, at which point the deflections at the beam tip are completely unbounded and a plastic hinge forms at the base of the beam. We want to determine the deflection of the beam anywhere in the beam and for any load from the fully elastic state to the collapse state.

Fully Elastic Solution

The problem of an elastic beam under a distributed load is straightforward. The differential equation describing a uniform beam under a distributed load $q(x)$ is given by

$$EI \frac{d^4 w}{dx^4} = q(x). \quad (1)$$

The solution to (1) is simply a matter of integrating (1) four times, yielding four constants of integration. Realizing that the beam has four boundary conditions (two on each side), these four constants can be uniquely determined and a unique solution can be found. In our example, the boundary conditions are

$$w(0) = 0, \quad w'(0) = 0, \quad M(L) = 0, \quad \text{and} \quad V(L) = 0, \quad (2)$$




Figure 1. Beam model.




Figure 2. Stress-strain curve for an elastic-perfectly plastic material.

where

$$M(x) = EI \frac{d^2 w}{dx^2} \quad \text{and} \quad V(x) = EI \frac{d^3 w}{dx^3}. \quad (3)$$

Integrating (1) twice with $q(x) = q_0$ and applying the boundary conditions at $x = L$, we find

$$M(x) = q_0 L^2 \left(\frac{x^2}{2L^2} - \frac{x}{L} + \frac{1}{2} \right). \quad (4)$$

Integrating (4) twice more and applying the fixed ended conditions yields

$$w(x) = \frac{q_0 x^2 L^2}{EI} \left(\frac{x^2}{24L^2} - \frac{x}{6L} + \frac{1}{4} \right) \quad (5)$$

for the displacement of the beam. Equation (5) provides the beam displacement anywhere in the beam under the assumption that the beam is comprised of a linearly elastic material.

Moment Due to a Partially Plastic Cross Section

In this section, we compute the moment that is the result of a partially plastic cross section. As the base of the beam goes from completely elastic to partially and subsequently fully plastic, the contribution of the stresses on the moment changes. We can quantify this easily by writing the stress distribution in a partially plastic section, as shown in Figure 3. The stress distribution shown in Figure 3 can be described analytically by

$$\sigma = \begin{cases} -\sigma_0, & h/2 \geq y \geq \eta, \\ -\sigma_0 y / \eta, & \eta \geq y \geq -\eta, \\ \sigma_0, & -\eta \leq y \leq -h/2. \end{cases} \quad (6)$$

The moment due to this distribution is

$$M_p(x) = 2b \int_0^{h/2} (-\sigma) y dy = 2b \int_0^\eta \sigma_0 \frac{y^2}{\eta} dy + 2b \int_\eta^{h/2} \sigma_0 y dy \quad (7)$$




Figure 3. Elastic and plastic zones in a partially plastic cross section.

or

$$M_p(x) = \frac{\sigma_0}{3} b \left(\frac{3h^2}{4} - \eta^2 \right), \quad (8)$$

where η is a function of x , and b is the width of the beam.

From equation (8) and Figure 3 it is seen that if $\eta = h/2$, the moment at that cross section has achieved the yield moment M_y , or

$$M_y = \frac{\sigma_0 b h^2}{6}. \quad (9)$$

Conversely, if the plastic region governed by $\eta(x)$ takes the value of zero, then the cross section has completely collapsed (section is fully plastic), and the moment is

$$M_c = \frac{\sigma_0 b h^2}{4}. \quad (10)$$

In the elastic-plastic region, the moment at any cross section is bounded by equations (9) and (10).

Displacements of an Elastic-Plastic Cantilever Beam

In this section we use the results of the last two sections to derive the expression for the beam displacements anywhere in the beam. To find the displacements, we match the moments of the elastic and elastic-plastic sections and integrate the resulting differential equation. The integration leads to an expression for the beam displacements.

Recalling the moment for the fully elastic case and equating it to the moment due to a partially plastic cross section, we see that

$$q_0 L^2 \left(\frac{x^2}{2L^2} - \frac{x}{L} + \frac{1}{2} \right) = \frac{\sigma_0}{3} b \left(\frac{3h^2}{4} - \eta^2 \right). \quad (11)$$

Solving for the variable η , which represents the size of the elastic core in an otherwise plastic region, we find

$$\eta = \left[\frac{3h^2}{4} - \frac{3q_0 L^2}{\sigma_0 b} \left(\frac{x^2}{2L^2} - \frac{x}{L} + \frac{1}{2} \right) \right]^{1/2}. \quad (12)$$

From (12), we can predict the extent of the plastic zone anywhere in the beam.

Next, we write that the strain due to bending of the plate is given by the expression

$$\epsilon = z \frac{d^2 w}{dx^2} = \frac{\sigma}{E}. \quad (13)$$

In regions of the beam where the cross section is partially plastic, equation (13) becomes

$$\frac{d^2 w_p}{dx^2} = \frac{\sigma_0}{Ez} = \frac{\sigma_0}{E\eta}. \quad (14)$$

Equation (14) provides a differential equation for the curvature of the beam in the partially plastic zone. The parameter η in (14) is given by equation (12). Thus, the differential equation to solve is

$$\frac{d^2 w_p}{dx^2} = \frac{\sigma_0}{E} \left[\frac{3h^2}{4} - \frac{3q_0 L^2}{\sigma_0 b} \left(\frac{x^2}{2L^2} - \frac{x}{L} + \frac{1}{2} \right) \right]^{-1/2} \quad (15)$$

subject to the boundary conditions

$$w_p(0) = 0 \quad \text{and} \quad w_p'(0) = 0. \quad (16)$$

The solution to (15) is not trivial, but it can be found analytically. Integrating (15) twice subject to the boundary conditions (16) yields

$$\begin{aligned} w_p(x) = & \frac{\sqrt{3}\sigma_0^2 b h}{3E q_0} \left\{ \frac{L}{h} \sqrt{\frac{2q_0}{\sigma_0 b}} \left(\frac{x}{L} - 1 \right) \sin^{-1} \left[\frac{L}{h} \sqrt{\frac{2q_0}{\sigma_0 b}} \left(\frac{x}{L} - 1 \right) \right] + \sqrt{1 - \frac{2q_0 L^2}{\sigma_0 h^2 b} \left(\frac{x}{L} - 1 \right)^2} \right. \\ & \left. + \frac{x}{h} \sqrt{\frac{2q_0}{\sigma_0 b}} \sin^{-1} \left(\frac{L}{h} \sqrt{\frac{2q_0}{\sigma_0 b}} \right) - \frac{L}{h} \sqrt{\frac{2q_0}{\sigma_0 b}} \sin^{-1} \left(\frac{L}{h} \sqrt{\frac{2q_0}{\sigma_0 b}} \right) - \left(1 - \frac{2q_0 L^2}{\sigma_0 b h^2} \right)^{1/2} \right\}. \quad (17) \end{aligned}$$

Equation (17) can only be used where the beam is partially (or fully) plastic. Recall that the elastic core in the plastic zone is denoted by the variable η . When $\eta = h/2$, the beam is entirely elastic. From equation (12), we see that this transition occurs at the location

$$\frac{x^*}{L} = 1 - \frac{h}{L} \sqrt{\frac{\sigma_0 b}{3q_0}}. \quad (18)$$

As long as the beam position is less than x^* , equation (17) can be used to compute the beam deflection.

Equation (17) provides the exact solution to the differential equation (15) subject to the boundary conditions (16) in the partially plastic zone. However, the entire beam is not in a plastic state; the majority of the beam is in a fully elastic state. For this region, we apply to the problem the traditional beam solution used earlier. If we compute the differential equation for a beam with no moment or shear at its end, we find

$$w'(x) = \frac{q_0 x L^2}{E b h^3} \left(2 \frac{x^2}{L^2} - 6 \frac{x}{L} + 6 \right) + C_3 \quad (19)$$

and

$$w(x) = \frac{q_0 x^2 L^2}{E b h^3} \left(\frac{x^2}{2L^2} - 2 \frac{x}{L} + 3 \right) + C_3 x + C_4. \quad (20)$$

To find the constants of integration C_3 and C_4 , we must apply the condition that the slope and displacement of the beam at the transition point x^* are equal in the partially plastic and fully elastic zones. That is, we compute the displacement in the plastic zone from (17) at the point x^* and set that equal to the displacement given by (20) at x^* . Additionally, we equate the slope of equation (19) to that of the derivative of (17) at x^* . The two conditions, then, yield expressions for the integration constants, such that

$$C_3 = -\frac{q_0 x^* L^2}{E b h^3} \left(2 \frac{x^{*2}}{L^2} - 6 \frac{x^*}{L} + 6 \right) + w_p'(x^*) \quad (21)$$

and

$$C_4 = -\frac{q_0 x^{*2} L^2}{E b h^3} \left(\frac{x^{*2}}{2L^2} - 2 \frac{x^*}{L} + 3 \right) - C_3 x^* + w_p(x^*) \quad (22)$$

where

$$w_p'(x) = \frac{\sqrt{3}\sigma_0^2 b h}{3E q_0} \left\{ \frac{1}{h} \sqrt{\frac{2q_0}{\sigma_0 b}} \sin^{-1} \left[\frac{L}{h} \sqrt{\frac{2q_0}{\sigma_0 b}} \left(\frac{x}{L} - 1 \right) \right] + \frac{1}{h} \sqrt{\frac{2q_0}{\sigma_0 b}} \sin^{-1} \left(\frac{L}{h} \sqrt{\frac{2q_0}{\sigma_0 b}} \right) \right\}. \quad (23)$$

To compute the displacements in the beam, we use equation (17) in the region $[0, x^*]$ and (20) in the region $[x^*, L]$.




Figure 4. Elastic-plastic cantilever beam model.

BUCKY Finite Element Model

To perform the plastic analysis numerically, the computer program BUCKY was used with its elastic-plastic analysis capabilities. Utilizing the tangent stiffness method of plasticity analysis, BUCKY is a p -version finite element method program capable of accurately predicting the response of simple structures to applied loads. The p -version finite element method is a highly accurate method that exploits the qualities of higher order smooth functions to describe large gradients. Traditional h -finite elements have a general lack of detail in this regard unless very fine meshing is employed.

The finite element model used to verify the plastic analysis of BUCKY is shown in Figure 4. Note that only two elements are employed in the solution of the problem. Obviously the p -method has the tremendous advantage of simplified modeling. The element labeled $E1$ has a size of the same order of the beam thickness. The small size of the element allows us to accurately trace the elastic-plastic boundary. The second element, $E2$, is much larger since we expect it to remain elastic. Even if this element were to become partially plastic, BUCKY would be able to effectively show this.

The physical parameters of the beam in Figure 4 are such that the length $L = 10$, the thickness $h = 2$, and the width $w = 1$. In addition, the beam material has some Young's modulus $E10E6$ associated with it, as well as a yield strength of $\sigma_0 = 50000$. Finally, since the material is elastic-perfectly plastic, the tangent modulus E_T is identically zero.

The load q_0 of Figure 4 is varied so that the beam can be compared to theoretical predictions at a variety of states. One caveat to the BUCKY analysis is that BUCKY is a two-dimensional finite element code, whereas the theory used to predict the beam deflection above is based upon a reduction from the full three-dimensional equations of elasticity to one dimension. The comparisons, however, will be shown to be close.

Comparison to Theoretical Results

There are four comparison points given by the loads $q_0 = 667$, $q_0 = 800$, $q_0 = 900$, and $q_0 = 1000$. For the beam under consideration, the load $q_0 = 667$ corresponds to the distributed load at which the beam first experiences a plastic effect. The first occurrence of a plastic component of stress is at the top and bottom outer fibers at the wall. The load $q_0 = 1000$ represents the theoretical collapse load of the beam. That is, at this load, the plate forms a fully plastic core and plastic hinge at the beam-wall interface. This gives unbounded deflections and the stiffness in some points of the beam quickly goes to zero. Numerically, this means singular element stiffness matrices, which is an undesirable effect.

At the moment the beam first reaches a yield point, the applied load takes the value $q_0 = 667$. At this point, the BUCKY analysis compares well to another benchmark, the PEGASYS finite element package. PEGASYS is a p -version finite element program based on secant modulus principles. However, both programs deviate from the elastic-plastic solution and fully elastic solution. Figure 5 shows the four deflections based on theoretical predictions for elastic, elastic-plastic, and the two computer programs. The deflections throughout the beam are shown.

As the load increases to $q_0 = 800$, the extent of the plastic zone increases somewhat. Figure 6 shows that the beam tip deflection increases slightly for an increase in the load q_0 . Whereas in the




Figure 5. Deflections of an elastic-perfectly plastic cantilever for $q_0=667$.




Figure 6. Deflections of an elastic-perfectly plastic cantilever for $q_0=800$.

first case where the theoretical predictions for the tip deflection were nearly equal for the elastic and plastic analysis, we now see in Figure 6 that the elastic solution underpredicts the deformation. This is because a linear elastic analysis cannot model material nonlinearities. We also see in Figure 6 that the two computer codes again give similar results.

As the load is increased further to $q_0 = 900$, BUCKY predicts the highest tip deflection. The deformations for this case are shown in Figure 7. Finally, in Figure 8, the deflections in the beam at full collapse are shown. The load at full collapse is $q_0 = 1000$. At this point, we see a close agreement between the theoretical predictions and the computer analysis. We also see that the PEGASYS code underpredicts the deformation slightly. Of course, the elastic solution trails well below the elastic-plastic solutions. As the material becomes plastic, the modulus decreases rapidly, resulting in larger deflections.

Finally, in Figure 9, we show the elastic-plastic boundary at the theoretical collapse load $q_0 = 1000$. The boundary is given by the light band on the left side of the beam. The plastic region is the darker area on the left side of the beam. Notice that the cross section at the wall is not completely plastic. Because of the manner in which the stress updates are generated at the element Gauss points, BUCKY can only compute an approximate stress at points deviating from the Gauss points. The stresses are found by determining an equation over the element which describes the stresses exactly at the Gauss points. All other points within the element have potential error. However, even though the stress distribution at the wall is not in a completely plastic state, the stress distribution throughout the beam does have the expected shape.




Figure 7. Deflections of an elastic-perfectly plastic cantilever for $q_0=900$.




Figure 8. Deflections of an elastic-perfectly plastic cantilever for $q_0=1000$.

Conclusions

As was seen from the example of the cantilever beam, the theoretical solution and the computer solution agree closely. At most, the tip deflections disagree by no more than a few percent. This error is remarkable considering that only two elements were used in the finite element analysis. Had more elements been utilized, the number of degrees of freedom would have increased and the error would have decreased further. Indeed, the BUCKY model could have been extended to four elements (two element by two element mesh) to trace the plastic boundary better.

From the example problem, it has been shown that BUCKY is an effective tool for the analysis of structures involving material nonlinearities. The p -version of the finite element method has proven its value with linear static analysis, and the same exceptional behavior is exhibited in nonlinear problems as well. By contrast, the convergence properties of traditional h -version finite elements yield poorer results for the same number of equations used in the BUCKY analysis.




Figure 9. Von Mises stress distribution at theoretical collapse load.

References

- [1] Burnett, David S., *Finite Element Analysis*, Addison-Wesley, 1987.
- [2] Cook, Robert D., *Concepts and Applications of Finite Element Analysis*, John Wiley & Sons, 1981.
- [3] Eisley, Joe G., *Mechanics of Elastic Structures*, Prentice Hall, 1989.
- [4] Hill, R., *The Mathematical Theory of Plasticity*, Clarendon Press, 1950.
- [5] Prager, W., *An Introduction to Plasticity*, Addison-Wesley, 1959.
- [6] Smith, James P., "BUCKY Instruction Manual," JSC-26385, September 1993.

REPORT DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE January 1994		3. REPORT TYPE AND DATES COVERED Technical Paper	
4. TITLE AND SUBTITLE Proof Test of the Computer Program BUCKY for Plasticity Problems				5. FUNDING NUMBERS 569422306	
6. AUTHOR(S) James P. Smith					
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Lyndon B. Johnson Space Center Houston, TX 77058				8. PERFORMING ORGANIZATION REPORT NUMBER S-753	
9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES) National Aeronautics and Space Administration Washington, D.C. 20546-001				10. SPONSORING / MONITORING AGENCY REPORT NUMBER NASA TP-3444	
11. SUPPLEMENTARY NOTES					
12a. DISTRIBUTION / AVAILABILITY STATEMENT Unclassified/Publicly Available National Technical Information Service 5285 Port Royal Road Springfield, VA 22161 (703) 487-4600 Subject Category: 39				12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) A theoretical equation describing the elastic-plastic deformation of a cantilever beam subject to a constant pressure is developed. The theoretical result is compared numerically to the computer program BUCKY for the case of an elastic-perfectly plastic specimen. It is shown that the theoretical and numerical results compare favorably in the plastic range. Comparisons are made to another research code to further validate the BUCKY results. This paper serves as a quality test for the computer program BUCKY developed at NASA Johnson Space Center.					
14. SUBJECT TERMS Plasticity, Computer Programs, Finite Element Method				15. NUMBER OF PAGES 9	
				16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT Unclassified	18. SECURITY CLASSIFICATION OF THIS PAGE Unclassified	19. SECURITY CLASSIFICATION OF ABSTRACT Unclassified	20. LIMITATION OF ABSTRACT UL		